



AT02-013

Straight tap spout brushed with brushed stainless tails

The Aquarius range incorporate simple and modern design, with the latest electronic functionality. Sensor operated for maximum hygiene and efficiency. 5 litres per minute integrated flow control. (Standard 5LPM, Other flow rates available) Automatic purge function, Sensor range adjustment, Wave on/wave off function, Anti Vandal and Lock Out functions, Chlorination function. Single mixed feed connection by 316 Stainless Steel tail (10mm). External TMV required.

Technical data

Type of tap	Aquarius WM straight
Material	316 Stainless steel
Surface finish	Brushed
Gross weight	1.15kg
Type of operation	No touch sensor
Type of mounting	Wall mounted
Type of mixing	Additional TMV may be required
Automatic purge	Yes* - Default: OFF / Options: 3, 6, 12, 24, 36 & 48 hours
Purge run time	Default 1 min* / Options: OFF, 30 secs, 1, 2, 4 & 8 mins
Spout projection / total tap length	170mm / 200mm
Minimum flow pressure	1.00 bar (Lower pressure station kits available)
Volume flow rate at 3 bar	5LPM (Other flow rates available)
Adjustable run time	Yes* - Default: 2 secs / Options: 2, 5, 10, 15, 20, 30 secs
Water connection	10mm 316 stainless steel tails
Anti-Vandal function	Yes
Lock out function	Default OFF / Options: OFF, 4, 6, 8 & 10 operations
Chlorination function	Yes* - Default 2 mins / Options: 1, 2, 3, 4, 5, 10, 20 & 30 mins
Battery or mains station kit	Single Battery: AT00-001 Single Mains: AT00-002 - Other options available. Contact KWC DVS.
Working pressure	1-10 Bar (For Low / High pressure, Contact KWC DVS.)
Max working temperature	60°C
Fixing	¾" BSP
Fixing length	Up to 30mm with flange nut

Brushed finish. Requires a Station kit to operate. Station kits available in Single Station Battery or Mains Single Station, 2 Station or 3 Station for multiple connections. Refer to Station kit data sheets.

Aquarius WM straight
316 Stainless steel
Brushed
1.15kg
No touch sensor
Wall mounted
Additional TMV may be required
Yes* - Default: OFF / Options: 3, 6, 12, 24, 36 & 48 hours
Default 1 min* / Options: OFF, 30 secs, 1, 2, 4 & 8 mins
170mm / 200mm
1.00 bar (Lower pressure station kits available)
5LPM (Other flow rates available)
Yes* - Default: 2 secs / Options: 2, 5, 10, 15, 20, 30 secs
10mm 316 stainless steel tails
Yes
Default OFF / Options: OFF, 4, 6, 8 & 10 operations
Yes* - Default 2 mins / Options: 1, 2, 3, 4, 5, 10, 20 & 30 mins
Single Battery: AT00-001 Single Mains: AT00-002 - Other options available. Contact KWC DVS.
1-10 Bar (For Low / High pressure, Contact KWC DVS.)
60°C
¾" BSP
Up to 30mm with flange nut